



Product Information

Mod.R&S 06 | Rev.4 | Update 10/2017 | Page 1



MODA VERNICE

Description PU plotter cut heat seal material with glossy varnish effect and polyester backing. The material is very thin and grants an easy cutting, weeding and application.
Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex (not suited for treated and sublimated textiles)

Usage

- Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the support cold



Average thickness
90 microns



Suggested cutting settings

blade new at 45°
pressure 40 gf
speed 30 cm/sec



Transfer settings
15 seconds at 150°C
(300°F)
medium pressure
(3-4 bar)

Washing

Wait at least **24 hours** from application before washing.
Washing resistance up to **30°C**, best inside-out.
Do not use bleach or other aggressive chemical agents.
Not suitable for dry cleaning
Not suitable for tumble dryer.

The product is REACH compliant

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience.
We recommend to perform a test before starting standard production.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System
ISO 9001:2015



www.tuv.com
ID 9105027958

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations.

Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

Thank you

Siser s.r.l.
Viale della Tecnica, 18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246

